


Gas ball valves, reduced bore

flange / flange, DN 100-500, reduced bore

Body	DN 100-500 Steel, P235GH (1.0345)
Ball	DN 100-500 Stainless steel, X5CrNi18-10 (1.4301)
Ball seal	DN 100-500 PTFE+C
Stem	DN 100-500 Stainless steel, X8CrNiS18-9 (1.4305)
Stem seal	DN 100-500 NBR
Operation	DN 100-500 Valve is equipped with manual gear
Flanges	EN 1092-1 Available PN 10, 16, 25, 40




Operation conditions
-40 °C – +70 °C
Over 70 °C contact manufacturer
Below -30 °C contact manufacturer
Lowest allowed ambient temperature -40 °C
Leakage rate A (EN 12266-1)




Not for steam

DN 100-600



DN 100-600



DN	PN	Product no.	A	B	C	D	D1	D2	D3	D4	E	H1	L	kg
100	16	280532	186	206	53	80	220.0	180.0	18.0	125.0	248	114	300	23.0
125	16	280533	224	216	53	100	250.0	210.0	18.0	200.0	258	112	325	30.0
150	16	280534	224	236	53	125	285.0	240.0	22.0	200.0	279	118	350	37.0
200	16	280536	268	244	69	150	340.0	295.0	22.0	250.0	293	92	400	68.0
250	16	280537	301	294	97	200	405.0	355.0	26.0	300.0	345	108	500	122.0
300	16	280538	363	343	118	250	460.0	410.0	26.0	500.0	412	115	500	190.0
350	16	280545	363	418	118	290	520.0	470.0	26.0	500.0	487	192	706	268.0
400	16	280539	440	500	138	340	580.0	525.0	30.0	500.0	573	242	810	365.0
500	16	280540	471	576	180	390	715.0	650.0	33.0	500.0	648	259	978	595.0