

Underjordiska kulventiler, fullt genomlopp

svetsning / svetsning, EN (DIN), DN 150-400, fullt genomlopp

Ventilhus	DN 150-350 Stål, P235GH (1.0345) DN 400 Stål, P355 NL1 (1.0566)/ GP240GH (1.0619)
Kula	DN 150-400 Rostfritt stål, X5CrNi18-10 (1.4301)
Kultätning	DN 150-400 PTFE+C
Spindel	DN 150-400 Rostfritt stål, X8CrNiS18-9 (1.4305)
Spindeltätning	DN 150-400 FPM
Topp av spindel	DN 150-400 Rostfritt stål, X5CrNi18-10 (1.4301)




Funktionsvillkor
-20 °C - +200 °C
Under -20 °C kontakta tillverkaren
Lägst tillåtna omgivningstemperatur -40°C
Läckageklass A (EN 12266-1)



Ej för ånga

DN 150-400



DN	PN	Product no.	D	D1	D2	D3	D4	H1	H2	H3	L	S	kg
150	25	23469405	150	168.3	273.0	76.1	35.0	490	406	334	400	4,5	62.0
200	25	23469505	200	219.1	355.6	76.1	40.0	525	415	327	530	5	105.0
250	25	23469605	250	273.0	457.0	88.9	50.0	580	443	331	550	5	143.0
300	25	23469705	290	323.9	508.0	114.3	50.0	603	440	329	686	5,6	167.0
350	25	23469805	340	355.6	610.0	168.3	70.0	680	502	350	762	6,3	308.0
400	25	23469905	390	406.0	660.0	178.0	90.0	720	516	350	1100	7,1	570.0